

	Type	L #	Hits	Search Text
1	BRS	L1	365079	(light or laser) and modulat\$4
2	BRS	L2	43076	pixel and 1
3	BRS	L3	6934	(scatering or scattered or scatter or defuse or defuser) and 2
4	BRS	L4	5113	pattern and 3
5	BRS	L5	4818	(optical or lens) and 4
6	BRS	L6	2008	controller and 5
7	BRS	L7	1093	(compensated or compensate or compensating) and 6

	DBs	Time Stamp	Comments	Error Definition
1	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	2007/01/04 14:25		
2	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	2007/01/04 14:26		
3	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	2007/01/04 14:27		
4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	2007/01/04 14:28		
5	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	2007/01/04 14:28		
6	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	2007/01/04 14:28		
7	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	2007/01/04 14:29		